

To compliment our extensive line of quality angiography accessories, Merit Medical has developed a complete line of high-pressure tubing to meet all procedural requirements.

Merit Tubing Line

Pressure Monitoring Tubing

1200 PSI (83 Bar) ExCite™ Tubing

1200 PSI (83 Bar) Clear Tubing

900 PSI (62 Bar) Clear Tubing

500 PSI (34 Bar) Clear Tubing

1200 PSI (83 Bar) Braided Tubing



Airless Rotator -

Merit Medical's patented airless rotator enhances patient safety by minimizing the possibility of trapped air.



Merit Keep™ -

Helps organize tubing and maintain better control of the sterile field.

.....

Merit's Keep provides the security of knowing the tubing will stay in place, without the worry of contamination of the sterile field. All flexible tubing styles are available with Merit's patented Keep feature.




Keep Tubing in Control

Merit offers an extensive line of clear,

PVC tubing styles rated at 1200, 900

and 500 PSI (83, 62 and 34 Bar).



Our color coded pressure monitoring tubing offers instant identification of specific monitor lines to help increase patient safety and decrease procedure time. Available only in our custom kits.



*Male Rotator
Luer Connector*

Allows 360° manipulation of the catheter without disconnection or tangling of the tubing lines.



*Female
Luer Connector*

Merit's stringent specifications provide consistent connectors and tubing maintaining our "quality first" reputation.



*Male Fixed
Luer Connector*

Assures secure connection to the catheter.

Specifications:	Merit	Merit Excite™	Merit Clear
Tubing Material	Flexible, braided polyurethane	Flexible nylon-polyurethane	Rigid PVC
Inner Diameter	.071" (1.8mm)	.071" (1.8mm)	.071" (1.8mm)
Pressure Rating	1200 PSI (84 Bar)	1200 PSI (84 Bar)	1200 PSI (84 Bar) 900 PSI (63 Bar) 500 PSI (35 Bar)
Fluid Capacity	10" (25cm) 0.71ml 20" (51cm) 1.36ml 30" (76cm) 2.01ml 48" (122cm) 3.18ml	10" (25cm) 0.71ml 20" (51cm) 1.36ml 30" (76cm) 2.01ml 39" (100cm) 2.59ml 48" (122cm) 3.18ml 59" (150cm) 3.88ml 72" (183cm) 4.73ml	10" (25cm) 1.00ml 20" (51cm) 1.99ml 30" (76cm) 2.99ml 48" (122cm) 4.78ml
Sterilization Method	ETO	ETO	ETO
Packaged	Coiled, 25 units per box, 4 boxes per case	Straight, 25 units per box, 4 boxes per case	Straight, 25 units per box, 4 boxes per case

H I G H P R E S S U R E T U B I N G C A T A L O G N U M B E R S :

**FLEXIBLE, BRAIDED, POLYURETHANE CONTRAST INJECTION LINE RATED AT 1200 PSI (83 BAR).
PACKAGED COILED, 25 UNITS PER BOX, 4 BOXES PER CASE.**

	10" Length (25cm)	20" Length (51cm)	30" Length (76cm)	48" Length (122cm)	72" Length (183cm)
Airless Rotating Adaptor With KEEP	HPF100E	HPF200E	HPF300E	HPF480E	HPF720E
Fixed Male Connector With KEEP	HPF101E	HPF201E HPF201K	HPF301E HPF301K	HPF481E HPF481K	HPF721E HPF721K

**CLEAR, PVC CONTRAST INJECTION LINE RATED AT 1200, 900, AND 500 PSI (83, 62, AND 34 BAR) .
PACKAGED STRAIGHT, 25 UNITS PER BOX, 4 BOXES PER CASE.**

	10" Length (25cm)	20" Length (51cm)	30" Length (76cm)	48" Length (122cm)
Airless Rotating Adaptor 1200 PSI (83Bar)	HPT100E	HPT200E	HPT300E	HPT480E
900 PSI (62Bar)	HP9100E	HP9200E	HP9300E	HP9480E
500 PSI (34Bar)	HP5100E	HP5200E	HP5300E	HP5480E
Fixed Male Connector 1200 PSI (83Bar)	HPT101E	HPT201E	HPT301E	HPT481E
900 PSI (62Bar)	HP9101E	HP9201E	HP9301E	HP9481E
500 PSI (34Bar)	HP5101E	HP5201E	HP5301E	HP5481E

**EXCITE™ FLEXIBLE, CLEAR NYLON/POLYURETHANE CO-EXTRUDED CONTRAST INJECTION LINE RATED AT 1200 PSI (83 BAR).
PACKAGED STRAIGHT, 25 UNITS PER BOX, 4 BOXES PER CASE.**

	10" Length (25cm)	20" Length (51cm)	30" Length (76cm)	39" Length (100cm)	48" Length (122cm)	59" Length (150cm)
Airless Rotating Adaptor	HPC100E	HPC200E	HPC300E	HPC390E	HPC480E	HPC590E
Fixed Male Connector	HPC101E	HPC201E	HPC301E	HPC391E	HPC481E	HPC591E

